

BEST A3

<http://www.lockreference.com>

MACS: 6
Increment: .018"
Progression: Single Step
E.P.D. .428"
Included Angle: 90°
Root Cut: .054"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #302
HPC Blitz	CX10
HPC Punch	N/A
ITL	55

Root Depths	
0	.318"
1	.300"
2	.282"
3	.264"
4	.246"
5	.228"
6	.210"

Spacing	
1	.088"
2	.238"
3	.388"
4	.538"
5	.688"
6	.838"
7	.988"

Notes
1) Read and cut tip-to-bow.
2) Discontinued; only sold to service existing systems.
3) 13C pins used for blockout cores.
4) MACS is technically 6 as there are no violations in system.

T.F.C: .088"

B.C.C: .150"

	0C	1C	2C	3C	4C	5C	6C			
Bottom Pins	.110"	.128"	.146"	.164"	.182"	.200"	.218"			
	13C									
	.343"									

	1D	2D	3D	4D	5D	6D	7D	8D	9D	10D
Master, Build-Up, & Top Pins	.018"	.036"	.054"	.072"	.090"	.108"	.126"	.144"	.162"	.180"
	11D	12D	13D							
	.198"	.216"	.234"							

Notes: