

# Yale .019"

<http://www.lockreference.com>

**MACS:** Varies  
**Increment:** .019"  
**Progression:** Two Step  
**E.P.D.** .502"  
**Included Angle:** Varies  
**Root Cut:** .054"

Key Origination	
Blackhawk	Card 208
CodeMax	DSD #72
HPC Blitz	C57
HPC Punch	N/A
ITL	476

Root Depths	
0	.320"
1	.301"
2	.282"
3	.263"
4	.244"
5	.225"
6	.206"
7	.187"
8	.168"
9	.149"

Spacing	
1	.200"
2	.365"
3	.530"
4	.695"
5	.860"
6	1.025"
7	1.190"

**T.F.C:** .200"  
**B.C.C:** .165"

Notes
1) Read and cut bow-to-tip.
2) Included angle can be 110°, 95°, or 86° to produce MACS of 4, 5, and 6, respectively.

	0	1	2	3	4	5	6	7	8	9
<b>Bottom Pins</b>	.182"	.201"	.220"	.239"	.258"	.277"	.296"	.315"	.334"	.353"
<b>Master Pins</b>			.038"	.057"	.076"	.095"	.114"	.133"	.152"	
<b>Top Pins</b>	.230"			.190"			.152"			.114"

## Notes: