

Russwin N Class (System 70)

<http://www.lockreference.com>

MACS: 4
Increment: .028"
Progression: Single Step
E.P.D. Varies
Included Angle: 90°
Root Cut: .053"

Key Origination	
Blackhawk	N/A
CodeMax	Varies
HPC Blitz	CX7
HPC Punch	N/A
ITL	378

Root Depths	
1	.334"
2	.306"
3	.278"
4	.250"
5	.222"
6	.194"

Spacing	
1	.250"
2	.406"
3	.562"
4	.718"
5	.874"
6	1.030"
7	1.186"

5 1/2	.208"
-------	-------

T.F.C.: .250"

B.C.C.: .156"

Notes
1) Read and cut bow-to-tip.
2) .509" diameter plugs have EPD of .499", .552" are .542"
3) For CodeMax, use DSD 77 for IC, DSD 3077 for Non-IC.
4) Use .320" top pin for PL5000 padlock and block master ring.

.509" Diameter

	1	2	3	4	5	6				
Bottom Pins	.165"	.193"	.220"	.248"	.276"	.305"				
Master Pins	.028"	.056"	.084"	.112"	.140"					
IC Top Pins	.192"	.163"	.135"	.107"	.080"	.080"				

* Standard top pin length is .171".

** Use .247" top pin for non-control chambers.

	-4	-3	-2	-1	0	+1	+2	+3	+4	+5
Build-Up Pins	.051"	.080"	.107"	.135"	.163"	.192"	.218"	.247"	.275"	.303"

.552" Diameter

	1	2	3	4	5	6				
Bottom Pins	.208"	.236"	.263"	.291"	.320"	.349"				
Master Pins	.028"	.056"	.084"	.112"	.140"					

* Standard top pin length is .171".

	-4	-3	-2	-1	0	+1	+2	+3	+4	+5
Build-Up Pins	.030"	.058"	.087"	.114"	.142"	.171"	.198"	.226"	.253"	.282"

Notes: