

Corbin Russwin Pyramid

<http://www.lockreference.com>

MACS: 7
Increment: .016"
Progression: Two Step
E.P.D. .466"
Included Angle: 90°
Root Cut: .053"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #17
HPC Blitz	CHS1
HPC Punch	PCH-1011
ITL	605

Root Depths	
0	.327"
1	.311"
2	.295"
3	.280"
4	.264"
5	.248"
6	.232"
7	.217"
8	.201"
9	.185"

Spacing	
1	.198"
2	.341"
3	.482"
4	.624"
5	.766"
6	.908"
7	1.049"

T.F.C: .198"
B.C.C: .1415"

Notes
1) Read and cut bow-to-tip.
2) Side Pin chambers are numbered bow-to-tip; right side 1-4, left side 6-9.
3) Pin diameters are .112".

	0	1	2	3	4	5	6	7	8	9
Bottom Pins	.139"	.155"	.171"	.187"	.202"	.218"	.234"	.250"	.265"	.281"
Master Pins			.031"	.047"	.063"	.078"	.094"	.110"	.126"	.141"
IC Top Pins	.189"	.173"	.157"	.141"	.126"	.110"	.094"	.078"	.063"	.047"

	-8	-7	-6	-5	-4	-3	-2	-1	0	+1
Build-Up Pins	.031"	.047"	.063"	.078"	.094"	.110"	.126"	.141"	.157"	.173"
	+2	+3	+4	+5	+6	+7	+8	+9		
	.189"	.204"	.220"	.236"	.252"	.267"	.283"	.299"		

*Conventional (Fixed Core): Use Top Pin A with plug totals 5,6,7,8,9. Use Top Pin C with plug totals 0,1,2,3,4.

*IC Non-Control Chambers: Use Top Pin B with plug totals 5,6,7,8,9. Use Top Pin C with plug totals 0,1,2,3,4.

	A	B	C
Top Pins	.141"	.204"	.236"

Notes: