

# Dexter

<http://www.lockreference.com>

**MACS:** 6  
**Increment:** .015"  
**Progression:** Two-Step  
**E.P.D.** .485"  
**Included Angle:** 100°  
**Root Cut:** .046"

Key Origination	
Blackhawk	Card 409
CodeMax	DSD #25
HPC Blitz	C16
HPC Punch	P16
ITL	142

Root Depths	
0	.320"
1	.305"
2	.290"
3	.275"
4	.260"
5	.245"
6	.230"
7	.215"
8	.200"
9	.185"

Spacing	
1	.216"
2	.371"
3	.526"
4	.681"
5	.836"
6	.991"

**T.F.C:** .216"  
**B.C.C:** .155"

Notes
1) Read and cut bow-to-tip
2) Blackhawk Card 409 lists depths 1-0, not 0-9.
3) Applies to Dexter large pin cylinders manufactured from 1969 on.

	0	1	2	3	4	5	6	7	8	9
<b>Bottom Pins</b>	.165"	.180"	.195"	.210"	.225"	.240"	.255"	.270"	.285"	.300"
<b>Master Pins</b>	-	-	.030"	.045"	.060"	.075"	.090"	.105"	.120"	.135"
<b>Top Pins</b>	.155"			.155"			.155"			

## Notes: