

# Kaba Peaks 140 Family A2

<http://www.lockreference.com>

<b>MACS:</b>	8
<b>Increment:</b>	.0125"
<b>Progression:</b>	Two Step
<b>E.P.D.</b>	Varies
<b>Included Angle:</b>	90°
<b>Root Cut:</b>	.046"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #608
HPC Blitz	CPKS1
HPC Punch	N/A
ITL	506

Root Depths	
0	.3187"
1	.3062"
2	.2937"
3	.2812"
4	.2687"
5	.2562"
6	.2437"
7	.2312"
8	.2187"
9	.2062"

Spacing	
1	.136"
2	.276"
3	.416"
4	.556"
5	.696"
6	.836"

**T.F.C:** .136"  
**B.C.C:** .140"

Notes
1) Keys are cut and read tip-to-bow.
2) E.P.D. for SFIC is .425", everything else is .488".
3) In position next to Peak, cuts deeper than a #6 require the use of an asymmetrical cutter, such as the #1011.
4) When master keying, the position closest to the Peak should be progressed last.
5) A stack height of 26 is standard for all Peaks cylinders except conventional mortise and rim cylinders (31) and SFIC (23).

	0A	1A	2A	3A	4A	5A	6A	7AS*	8AS*	9AS*
<b>A Series Bottom Pins</b>	.107"	.1195"	.132"	.1445"	.157"	.1695"	.182"	.1945"	.207"	.2195"

	0J	1J	2JS*	3JS*	4JS*	5J	6J	7J	8J	9J
<b>J Series Bottom Pins</b>	.1695"	.182"	.1945"	.207"	.2195"	.2325"	.2445"	.257"	.2695"	.282"

\* "S" indicates spool type bottom pins.

\*\* J Series bottom pins are for large diameter plugs only. 0J thru 4JS are the same as 5A thru 9AS, respectively.

\*\*\* Bottom pins are .003" shorter than aftermarket replacement pins.

Master, Build-Up, & Top Pins	2B	3B	4B	5B	6BS*	7B	8BS*	9B	10BS*	11B
	.025"	.0375"	.050"	.0625"	.075"	.0875"	.100"	.1125"	.125"	.1375"
	.150"	.1625"	.175"	.1875"	.200"	.2125"	.225"	.2375"		

\* "S" indicates spool type top pins.

## Notes: