

Kaba Peaks 150 Family A4

<http://www.lockreference.com>

MACS: 5
Increment: .021"
Progression: Single Step
E.P.D. .425"
Included Angle: 90°
Root Cut: .046"

Key Origination	
Blackhawk	N/A
CodeMax	See notes.
HPC Blitz	N/A
HPC Punch	N/A
ITL	See notes.

Root Depths	
0	.318"
1	.297"
2	.276"
3	.255"
4	.234"
5	.213"

Spacing	
1	.086"
2	.236"
3	.386"
4	.536"
5	.686"
6	.836"
7	.986"

Notes
1) Keys are cut and read tip-to-bow.
2) In position next to Peak, cuts deeper than a #3 require the use of an asymmetrical cutter, such as the #1011.
3) When master keying, the position closest to the Peak should be progressed last.
4) For Codemax, use DSD #615 for 6 pin, DSD #616 for 7 pin.
5) For ITL, use ITL# 277 for 6 pin, ITL# 276 for 7 pin.

T.F.C: .086"

B.C.C: .150"

	0E	1E	2E	3E	4ES*	5ES*				
E Series Bottom Pins	.107"	.128"	.149"	.1695"	.191"	.212"				

	0K	1KS*	2KS*	3K	4K	5K				
K Series Bottom Pins	.1695"	.191"	.212"	.2325"	.254"	.275"				

* "S" indicates spool type bottom pins.

** Bottom pins are .003" shorter than aftermarket replacement pins.

Master, Build-Up, & Top Pins	1F	2F	3F	4FS*	5FS*	6FS*	7F	8F	9F	10F
	.021"	.042"	.063"	.084"	.105"	.125"	.147"	.168"	.189"	.210"
	.231"									

* "S" indicates spool type top pins.

Notes: