

Corbin Russwin Access 3 (AS & AHS)

<http://www.lockreference.com>

MACS: 4
Increment: .030"
Progression: Single Step
E.P.D. .509"
Included Angle: 86°
Root Cut: .015"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #392
HPC Blitz	C392
HPC Punch	N/A
ITL	N/A

Root Depths*		
Number	Actual	Reference
1	.271"	.259"
2	.241"	.229"
3	.211"	.199"
4	.181"	.169"
5	.151"	.139"
6	.121"	.109"

Spacing	
1	.244"
2	.414"
3	.584"
4	.754"
5	.924"
6	1.094"

Notes
1) Read and cut bow-to-tip.
2) AS & AHS bottom bins are chisel tipped and rotate up to 20° from perpendicular.
3) Actual depths are as measured with a micrometer.

	Left	Center	Right
Cut Angles	-20°	0°	+20°

T.F.C: .244"

B.C.C: .170"

	1	2	3	4	5	6	7	8	9	
Bottom Pins	.231"	.261"	.291"	.321"	.351"	.381"				
Master Pins	.030"	.060"	.090"	.120"	.150"					
Top Pins	.030"	.060"	.090"	.120"	.150"	.180"	.210"	.240"	.270"	

	1	2	3	4	5	6	7	8	9	
Control Drivers (LFIC)	.030"	.060"	.090"	.120"	.150"	N/A	.210"	.240"	.270"	
	10	11								
	.300"	.330"								

*Access 3 cylinders have constant plug totals. For fixed cores and non-control chambers in LFIC stack height is 10, for LFIC control chambers stack height is 13.

Notes: