

Kwikset Titan

<http://www.lockreference.com>

MACS: 4
Increment: .023"
Progression: Single Step
E.P.D. .498"
Included Angle: 90°
Root Cut: .084"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #94
HPC Blitz	C31X
HPC Punch	P31X
ITL	250

Root Depths	
1	.329"
2	.306"
3	.283"
4	.260"
5	.237"
6	.214"
7	.191"

Spacing	
1	.097"
2	.247"
3	.397"
4	.547"
5	.697"
6	.847"

T.F.C: .097"

B.C.C: .150"

Notes
<p>1) Read and cut bow-to-tip.</p> <p>2) Use .160" length top pins for construction keying.</p> <p>3) 7th depth used in factory generated, non-SmartKey systems.</p> <p>4) Rekeying notch is cut on the back edge of the key. The notch is .249" deep, with a flat .188" wide starting .228" from the shoulder and extending towards the tip.</p> <p>5) When using Kwikset original (flat nose) pins in position 1, the cut flat must be extended fully to the shoulder.</p>

	1	2	3	4	5	6	7			
Bottom Pins	.172"	.195"	.218"	.241"	.264"	.287"	.310"			
Master Pins	.023"	.046"	.069"	.092"	.115"	.138"				
Top Pins	.180"									

*Titan uses the same pins as Kwikset Classic. Spool top pins are available in both .180" and .160" lengths but are rarely used in factory combined locks.

Notes: