

Medeco X4

<http://www.lockreference.com>

MACS: 9
Increment: .0125"
Progression: Two Step
E.P.D. Varies
Included Angle: 90°
Root Cut: .054"

Key Origination	
Blackhawk	N/A
CodeMax	DSD #1200
HPC Blitz	C3
HPC Punch	P3
ITL	311

Root Depths	
0	.3180"
1	.3055"
2	.2930"
3	.2805"
4	.2680"
5	.2555"
6	.2430"
7	.2305"
8	.2180"
9	.2055"

Spacing (Shoulder)	
1	.195"
2	.345"
3	.495"
4	.645"
5	.795"
6	.945"
7	1.095"

Notes
1) Read and cut tip-to-bow.
2) Originally sold as Keymark X4.
3) Tip stop used for SFIC.
4) Shoulder stop used for all other cores/cylinders.
5) SFIC, Corbin Russwin/Sargent LFIC, and cam locks have a plug diameter of .434".
6) Conventional cylinders and Schlage/Yale LFIC have a plug diameter of .511".
7) Pin stack total for SFIC is 23.
8) Pin stack total for non-SFIC is 19.

T.F.C: Varies
B.C.C: .150"

Spacing (Tip)	
1	.090"
2	.240"
3	.390"
4	.540"
5	.690"
6	.840"
7	.990"

.434" Diameter

	0	1	2	3	4	5	6	7*	8*	9*
Bottom Pins	.110"	.1225"	.135"	.1475"	.160"	.1725"	.185"	.1975"	.210"	.2225"

* Available in spool variation.

.511" Diameter

	0	1	2	3	4	5	6	7*	8*	9*
Bottom Pins	.1860"	.1985"	.2110"	.2235"	.2360"	.2485"	.2610"	.2735"	.2860"	.2985"

* Available in spool variation.

	2	3	4	5	6*	7	8*	9	10*	11
Master, Build-Up, & Top Pins	.025"	.0375"	.050"	.0625"	.075"	.0875"	.100"	.1125"	.125"	.1375"
	12	13	14	15	16	17	18	19		
	.150"	.1625"	.175"	.1875"	.200"	.2125"	.225"	.2375"		

* Available in spool variation.

Notes: