

# S&G 44XX Renter

<http://www.lockreference.com>

Key Origination	
Blackhawk	N/A
CodeMax	DSD #555
HPC Blitz	CSD40
HPC Punch	N/A
ITL	385

Spacing	
1	.167"
2	.222"
3	.271"
4	.319"
5	.367"
6	.422"
Throat	1.0875"

Cut Width	
1	.066"
2	.052"
3	.052"
4	.052"
5	.052"
6	.066"
Throat	.105"

Notes
1) Read and cut tip-to-bow.
2) Spacing is from front of tip-stop to center-of-cut.
3) Use DSD #1555 for throat cut., use modified horseshoe tip stop HPC HT-SD or equivalent.
4) For ITL, cuts 7 and 8 are throat cut.

Root Depths	
0	.314"
1	.298"
2	.278"
3	.258"
4	.238"
5	.218"
6	.198"
7	.178"
Throat	.235"

	Blanks			
	4440	4442	4443	4444
<b>S&amp;G</b>	96	60	60	96
<b>Ilco</b>	1063E	1063B	1063B	1063E
<b>Jet</b>	S&G-3-NS	S&G-2-NS	S&G-2-NS	S&G-3-NS

**Blade Height\*:** .315" .390"/.315" .390"/.315" .315"

**Tip Height:** .070" .070" .070" .070"

\*Where two heights are shown, the first number is the height closest to the bow and the second is the height closer to the tip.

## Notes: