

Schlage Primus/Primus XP/Everest Primus

<http://www.lockreference.com>

MACS: 7
Increment: 0.15"
Progression: Two Step
E.P.D. .500"
Included Angle: 100°
Root Cut: .031"

Key Origination	
Blackhawk	Card 198
CodeMax	DSD #60
HPC Blitz	C45
HPC Punch	P45
ITL	391

Root Depths	
0	.335"
1	.320"
2	.305"
3	.290"
4	.275"
5	.260"
6	.245"
7	.230"
8	.215"
9	.200"

Spacing	
1	.231"
2	.387"
3	.543"
4	.699"
5	.855"
6	1.011"

T.F.C: .231"

B.C.C: .156"

Notes
1) Read and cut tip-to-bow.
2) Applies to Primus, Primus XP, Everest Primus, Everest Primus XP, Everest 29 Primus, and Everest 29 Primus XP.
3) Finger Pin #7 is only used in XP systems.

Side Biting Spacing			
	Left	Center	Right
1	.277"	.309"	.341"
2	.433"	.465"	.497"
3	.589"	.621"	.653"
4	.745"	.777"	.809"
5	.901"	.933"	.965"

Side Biting Root Depths			
	Left	Center	Right
Extra Shallow	.072"	-	.072"
Shallow	.048"	.060"	.048"
Deep	.024"	.036"	.024"

Finger Pin Number			
	Left	Center	Right
Extra Shallow	-	-	7
Shallow	1	3	5
Deep	2	4	6

	0	1	2	3	4	5	6	7	8	9
Bottom Pins	.165"	.180"	.195"	.210"	.225"	.240"	.255"	.270"	.285"	.300"
Master Pins			.030"	.045"	.060"	.075"	.090"	.105"	.120"	
Top Pins	.235"				.200"			.165"		

Notes: