

# Kwikset .023"

<http://www.lockreference.com>

**MACS:** 4  
**Increment:** .023"  
**Progression:** Single Step  
**E.P.D.** .501"  
**Included Angle:** 90°  
**Root Cut:** .084"

Key Origination	
Blackhawk	Card 407
CodeMax	DSD #46
HPC Blitz	C31
HPC Punch	P31
ITL	265

Root Depths	
1	.329"
2	.306"
3	.283"
4	.260"
5	.237"
6	.214"
7	.191"

Spacing	
1	.247"
2	.397"
3	.547"
4	.697"
5	.847"

**T.F.C:** .247"

**B.C.C:** .150"

Notes
1) Read and cut bow-to-tip. 2) Use .160" length top pins for construction and master keying. 3) Used in Corbin 80/Ruswin 751 residential keyways between 1966 - 1992 under "K Class" name. 5) 7th depth used in factory generated master key systems, not usable in SmartKey. No factory #7 pins exist. 6) Factory plugs are .498" diameter but bevels in pins and plug allow a ±.007" variance in EPD (.491"-.505").

	1	2	3	4	5	6	7			
<b>Bottom Pins</b>	.172"	.195"	.218"	.241"	.264"	.287"				
<b>Master Pins</b>	.023"	.046"	.069"	.092"	.115"	.138"				
<b>Top Pins</b>	.180"						.160"			

## Notes: